



# Racan Premium Anti-Rodent Sealant

INDOOR & OUTDOOR RODENT CONTROL

- ✓ Seals joints, cracks, seams and holes to prevent rodent access
- ✓ Metal shavings to prevent rodents chewing
- ✓ Long-lasting, waterproof protection
- ✓ Ready to paint over once dry
- ✓ Non-toxic, poison-free
- ✓ Metal Detectable

## Directions for use

1. Carefully cut the top off the tube using a knife. Fix the nozzle to the tube and screw it on tightly. If required, you can carefully trim the nozzle further to give a thicker application of sealant.
2. Apply the sealant with a caulking gun (image A); make sure the layer depth of the sealant is at least 15 mm and that the gap is completely filled to the edges on all sides.
3. Smooth the applied sealant with a pallet knife or equivalent tool for a smooth finish. (image B).
4. Seal is instantly waterproof and instantly effective (image C).



Image A



Image B



Image C



**RACAN**

Contents: 300 ml.



Scan Here  
for more  
information

**WHERE TO USE:** Use this sealant around joints, pipe holes, cracks, holes and seams. Can also be used to seal gaps in walls, floors and roof sections.

**USER NOTES:** Use of gloves is recommended. This sealant should be used on openings/ducts of at least 5mm. Clean hands and tools with a dry cloth after use, if necessary use white spirit. The sealant should be fully dry after 48 hours (at 20°C). Please note: this sealant remains soft to the touch after application. For best results, also remove any nearby food sources to prevent rodents trying to gain entry.

**DISPOSAL:** After using this product, dispose of contents/container in normal household waste. However, if used in a place of work, any products and empty container must be disposed of as controlled waste.

**PRECAUTIONS: READ ALL INSTRUCTIONS BEFORE USE. Keep out of the reach of children.**

Although this product is non-toxic, it should be kept away from children and pets. Avoid contact with eyes and mouth. Not suitable for consumption. Do not apply near sources of heat.

Can be painted after 48 hours (at 20°C). Store in a dry, frost-free place.

Processing temperature -25°C to +50°C. The required layer depth may vary, several applications may be needed for a secure barrier.



**LodiUK**

Marketed by: Lodi UK Limited  
Building 69, Third Avenue, Pensnett Trading  
Estate, Kingswinford, West Midlands DY6 7FD.  
01384 404242, sales@lodi-uk.com  
[www.lodi-uk.com](http://www.lodi-uk.com)  
LODI S.A. P.A. des Quatre Routes  
35390 Grand Fougeray FRANCE

