

300 mm

80 mm

DANGER



PLP489


Marketed by: Lodi UK Ltd
Unit 104, Potter Space,
7 Kidderminster Road,
Cutnall Green,
Droitwich WR9 0NS
Tel: 01384 404242
Email: sales@lodi-uk.com
www.lodi-uk.com

Contains 2-phenylphenol 30.00% w/w and potassium chlorate
Harmful if swallowed
Causes severe skin burns and eye damage
May cause an allergic skin reaction
Suspected of causing cancer
Very toxic to aquatic life with long lasting effects.

Safety information:
Obtain special instructions before use
Do not breathe dust / smoke
Wear protective gloves/eye protection.
IF exposed or concerned: Get medical advice/attention
Dispose of contents/container in accordance with local regulations

Authorisation holder:
Octavius Hunt Ltd, Dove Lane,
Redfield, Bristol, BS5 9NQ

 **LodiUK** UFI: 4M60-U0UE-W00R-A223 HSE 10349
Expiry date: 2 years from date of manufacture.



OPP

DISINFECTANT

SMOKE



250G

PROFESSIONAL USE
APPLICATION COVERAGE: 250m³
READ ALL PRECAUTIONS BEFORE USE!

Aerial disinfectant for fungicidal, bactericidal and virucidal treatment of empty animal and storage areas and equipment.

TREATMENT:
Dose: 300 mg Orthophenylphenol / m³

INSTRUCTIONS FOR USE:
Close all mechanical ventilation, windows and doors (except exit door) before treatment and isolate smoke alarms for the minimum duration of the treatment. Clear people, plants, animals, including fish, flammable goods and any food stuffs from the area to be treated. Cover all water storage tanks before application.
Place each generator on a cleared heatproof surface not less than 1M X 1M with a minimum ceiling height of 3M.
If more than one generator is required, distribute them evenly in the treatment area before lighting.
Remove lid, light exposed tip of the igniter and leave the area. Light multiple generators in sequence starting furthest from the exit.
In situations where it is not possible to vacate the treatment area immediately after ignition, wear suitable protective clothing (coveralls) and suitable respiratory equipment.
The area being treated should remain completely sealed for a minimum of 4 hours, maximum efficacy is achieved at 15 hours.
Ventilate thoroughly for at least 30 minutes before entering the premises without respiratory protection.
The generator will become very hot during use and the volume of smoke produced may trigger smoke detectors.